Quotation Request //

US Government Printing Office

Agency Publishing Services 732 North Capitol Street, NW Washington DC 20401-0001 **JACKET:327-432**

Issue Date and Time: 09/25/2006 5:37 PM

Quotations are Due By:

(Eastern Time)10:00 AM on 09/26/2006

Submit Fax Quotes to: 00000000

TITLE: Your Guide To Electronic Information at FERC.

QUANTITY: 10000 copies, +/- none. **TRIM SIZE:** 16 x 9" flat, 4 x 9" folded.

PAGES: Face and back

SCHEDULE:

Furnished Material will be available for pickup by 09/26/2006 Deliver complete (to arrive at destination) by 10/05/2006

F.O.B. destination

QUALITY LEVEL: 2 Quality Assurance Through Attributes (GPO PUB 310.1, effective May 1979 (Rev. 8-02)) applies. **DESCRIPTION:**

RESTRICTED PRODUCTION AREA: THIS ORDER MUST BE PRODUCED WITHIN A 50 MILE RADIUS OF ZERO MILESTONE, WASHINGTON, DC.

Face and back form printing head to head with 4-color process illustrations, artwork and background areas created out of tints and solids of the process colors, and with black type, some overprinting background areas.

MATERIAL FURNISHED: Contractor to pickup at GPO. One CD ROM created on a Macintosh system using Adobe InDesign CS2, Adobe Illustrator CS2, and Adobe Photoshop CS2 with files in native application format. All printer and screen fonts are included in the files. Contractor must make all reproducibles required.

Prior to image processing, the contractor is responsible for performing a basic check (preflight) of the furnished publishing files to assure accurate output of the required reproduction image. Any errors, media damage or data corruption that might interfere with proper file imaging must be reported to the contract administrator in sufficient time to comply with the shipping schedule. In addition, the contractor is responsible for creating or altering any necessary trapping, setting proper screen angles and screen frequency, and defining file output selection for the imaging devise being utilized. All furnished files must be imaged as necessary to meet assigned quality level.

A set of full color laser proofs.

A printed folding dummy.

PAPER: * Must be in accordance with JCP Paper Specification Standards in effect on date of this order JCP Code* L62, No. 2 White Coated Cover, Dull-Finish, Basis Size 20 X 26" Basis Weight 80 lbs.

COLOR OF INK: Ink Must Contain a Minimum of 20% Vegetable Oil

4-color process

PRINT PAGE: Head to Head

MARGINS:

Inadequate gripper margins, bleeds all sides with uncommon bleeds; follow furnished files.

PROOFS:

PRESS SHEET INSPECTION REQUIRED. CONTRACTOR MUST CALL (202) 512-1162 WITH 72 HOURS NOTICE.

Final makeready press sheets will be inspected and approved at the contractor's plant for the purpose of establishing specified standards for use during the actual press run. Upon approval of the sheets, contractor is charged with maintaining those standards throughout the press run (within QATAP tolerances when applicable) and with discarding all makeready sheets that preceded approval. See GPO Publication 315.3 (Guidelines for Contractors Holding Press Sheet Inspections) dated July 1994. Note: A press sheet inspection is for the purpose of setting specific standards that are to be maintained throughout the entire run. It does

Page 1 of 2 GPO Contract Terms (GPO Pub. 310.2, effective December 1, 1987 (Rev. 6-01)) applies. Reports of Fraud, Waste, and Abuse can be made in strict confidence to the GPO Inspector General toll-free National Hotline 1-800-743-7574.

JACKET: 327432 FEDERAL ENERGY REGULATORY COMMISSIO 6-00136 BAC: 6717 01

Your Contract Administrator is: Call: Written By: fyator Reviewed By:

not constitute a prior approval of the entire run.

Press sheets must contain control bars for each color of ink on the sheet. Control bars must be placed parallel to the press's ink rollers. The control bars must show areas consisting of 5 x 5 mm (3/16 x 3/16") minimum solid color patches; tint patches of 25, 50, and 75%; dot gain scale (such as, BRUNNER, GATF, GRETAG, or RIT); and gray balance patches for process color (if applicable). These areas must be repeated across the entire press sheet.

BINDING:

Trim four sides. Fold from 16 x 9" to 8 x 9" and than fold again to 4 x 9" using two parallel folds, with title out. Follow folding dummy.

PACKING:

Shrink-film wrap in suitable units and pack suitably in shipping containers.

DISTRIBUTION:

Deliver 10,000 copies (includes 80 Departmental Random "Blue Label" copies) and furnished material to FERC, 888 First Street, NE, Attn: Carlton Jackson/Publishing Services 3P-6, Washington, DC 20426. Inside Delivery Required.

QUALITY ASSURANCE STANDARDS: The following standards shall apply to these specifications:

Inspection Levels (from ANSI/ASQC Z1.4):

- (a) Non-destructive Tests -- General Inspection Level 1.
- (b) Destructive Tests -- Special Inspection Level S-2.

Specified standards to correspond with each required attribute as follows:

ATTRIBUTE Specified Standard

P-7. Type Quality and Uniformity
O.K.'d Press Sheets
P-10. Process Color Match
O.K.'d Press Sheets

Special Instructions: In the event that inspection of press sheets is waived by the Government, the following listed alternate standards (in order of precedence) shall become the Specified Standards:

P-7. Type Quality and Uniformity Furnished electronic media P-10. Process Color Match Furnished electronic media

JACKET: 327432 FEDERAL ENERGY REGULATORY COMMISSIO 6-00136 BAC: 6717 01

Your Contract Administrator is: Call: Written By: fyator Reviewed By: